



訂貨型號 Order Code		鏜孔範圍 Boring range ØD	刀柄型號 shank model	L1	H
8支組 (標準) 8pcs (standard)	BT40-NBJ16-8P	8-50	BT40-ECK5-60	60	60
	BT50-NBJ16-8P		BT50-ECK5-75	75	
	SK40-NBJ16-8P		SK40-ECK5-65	65	
	SK50-NBJ16-8P		SK50-ECK5-75	75	
	DIN2080-40-NBJ16-8P		DIN2080-40-ECK5-60	60	
	DIN2080-50-NBJ16-8P		DIN2080-50-ECK5-75	75	
	HSK-A63-NBJ16-8P		HSK-A63-ECK5-75	75	
	HSK-A100-NBJ16-8P		HSK-A100-ECK5-75	75	
	BT40-NBJ16-12P	6-55	BT40-ECK5-60	60	60
	BT50-NBJ16-12P		BT50-ECK5-75	75	
	SK40-NBJ16-12P		SK40-ECK5-65	65	
	SK50-NBJ16-12P		SK50-ECK5-75	75	
	DIN2080-40-NBJ16-12P		DIN2080-40-ECK5-60	60	
	DIN2080-50-NBJ16-12P		DIN2080-50-ECK5-75	75	
	HSK-A63-NBJ16-12P		HSK-A63-ECK5-75	75	
	HSK-A100-NBJ16-12P		HSK-A100-ECK5-75	75	

▲ 以上規格為整套組合，也可單獨訂購刀柄及刀杆，請在訂購時注明具體規格！

The above specification is a tool package, a single order for heads or shanks is also available, please specify the details when ordering.



鏜刀杆規格 (標準型)

Boring shank specifications(standard type)

鏜刀杆規格 Boring shank spec.	鏜孔範圍 Boring range ØD	深度 Depth M	刀片規格 Insert type	刀片螺絲 Insert Screw	扳手 Wrench	切入量 Cutting volume ap	進給量 Feed F
BJ1606-20	6-9	20	WBGT060102L	CSTB-2	T6	0.05-0.2	0.05-0.1
BJ1608-28※	8-11	28	TBGT060102L			0.05-0.2	0.05-0.1
BJ1610-36※	10-13	36	TBGT060104L			0.1-0.25	0.07-0.15
BJ1612-42※	12-17	42	TPGT090202L	CSTB-2.5	T8	0.05-0.2	0.05-0.1
BJ1614-50	14-19	50					
BJ1616-60※	16-21	60					
BJ1620-63※	20-26	63	TPGT090204L			0.1-0.25	0.07-0.15
BJ1624-64※	24-31	64					
BJ1630-72※	30-40	72					
BJ1635-72	35-45	72					
BJ1640-72※	40-50	72					
BJ1645-72	45-55	72					



鏜刀杆規格 (加長型)

Boring shank specifications(extension type)

鏜刀杆規格 Boring shank spec.	鏜孔範圍 Boring range ØD	深度 Depth M	刀片規格 Insert type	刀片螺絲 Insert Screw	扳手 Wrench	切入量 Cutting volume ap	進給量 Feed F
BJ1606-24L	6-9	24	WBGT060102L	CSTB-2	T6	0.05-0.2	0.05-0.1
BJ1608-32L※	8-11	32	TBGT060102L			0.05-0.2	0.05-0.1
BJ1610-40L※	10-13	40	TBGT060104L			0.1-0.25	0.07-0.15
BJ1612-53L※	12-17	53	TPGT090202L	CSTB-2.5	T8	0.05-0.2	0.05-0.1
BJ1614-60L	14-19	60					
BJ1616-68L※	16-21	68					
BJ1620-83L※	20-26	83	TPGT090204L			0.1-0.25	0.07-0.15
BJ1624-90L※	24-31	90					
BJ1630-90L※	30-40	90					
BJ1635-90L	35-45	90					
BJ1640-90L※	40-50	90					
BJ1645-90L	45-55	90					

★ 鏜刀杆規格帶※的為標準8支組合。

★ 以上規格為整套組合，也可單獨訂購刀柄及刀杆，請在訂購時注明具體規格。

★ 鏜刀杆材質有高速鋼和合金鋼可供選擇。

★ Boring shanks with mark "※" are a standard package.(8 pieces in a set)

★ The above specification is a tool package,a single order for heads or shanks is also available.Please specify the details when ordering.

★ The boring shank material are available in high speed steel and alloy steel.



訂貨型號 Order Code		鏜孔範圍 Boring range ØD	刀柄型號 shank model	L1	H
8支組 (標準) 8 pcs (standard)	BT30-NBJ12-8P	6-24	BT30-ECK4-45	45	48
	BT40-NBJ12-8P		BT40-ECK4-60	60	
	BT50-NBJ12-8P		BT50-ECK4-75	75	
	SK40-NBJ12-8P		SK40-ECK4-65	65	
	SK50-NBJ12-8P		SK50-ECK4-75	75	
	DIN2080-40-NBJ12-8P		DIN2080-40-ECK4-60	60	
	DIN2080-50-NBJ12-8P		DIN2080-50-ECK4-75	75	
	HSK-A63-NBJ12-8P		HSK-A63-ECK4-75	75	

▲ 以上規格為整套組合，也可單獨訂購刀柄及刀杆，請在訂購時注明具體規格！
The above specification is a tool package, a single order for heads or shanks is also available, please specify the details when ordering.



鏜刀杆規格 (標準型)

Boring shank specifications(standard type)

鏜刀杆規格 Boring shank spec.	鏜孔範圍 Boring range ØD	深度 Depth M	刀片規格 Insert type	刀片螺絲 Insert Screw	扳手 Wrench	切入量 Cutting volume ap	進給量 Feed F
BJ1206-24	6-10	24	WBGT060104	CSTB-2	T6	0.05-0.2	0.05-0.1
BJ1208-32	8-12	32	TBGT060104			0.05-0.2	0.05-0.1
BJ1210-40	10-14	40				0.1-0.25	0.07-0.15
BJ1212-45	12-16	45	TBGT090204	CSTB-2.5	T8	0.05-0.2	0.05-0.1
BJ1214-45	14-18	45					
BJ1216-45	16-20	45					
BJ1218-45	18-22	45					
BJ1220-45	20-24	45					

- ★ 以上規格為整套組合，也可單獨訂購刀柄及刀杆，請在訂購時注明具體規格。
- ★ 鏜刀杆材質有高速鋼和合金鋼可供選擇。
- ★ The above specification is a tool package, a single order for heads or shanks is also available. Please specify the details when ordering.
- ★ The boring shank material are available in high speed steel and alloy steel.