

**SPECIFICATION**

UNIT: mm / inch

**HF -1500 / 2000 / 2500**

CAPACITY	Swing over bed	1500 / 2000 / 2500
	Swing over cross slide	1100 / 1600 / 2100
	Z-axes travel	1000
BED	Swing over gap	1900 / 2400 / 2900
	Width of bed	2010 (79")
	Length of bed	1150 / 1650
	Bed way	3 ways
HEADSTOCK	Spindle bore diameter	152(6") / OP: 230 (9")
	Numbered of spindle speeds	16 steps
	Range of spindle speeds	4~420 rpm
	Spindle nose	ASA A2-11 / OP: A2-15 / A2-20
	Top slide travel (Compound rest travel)	370 (14.57")
	Max. Size cutting size	40 x 40 (1.57" x 1.57")
MOTOR	Main spindle motor	30 HP (22.5 kw)
	Coolant pump motor	1/8 HP (0.1 kw)
COLOR	Upper parts + Lower parts	Light gray white RAL-7035 + Blue RAL-5015

※ We reserve the right to modify &amp; improve our products without notice.

**STANDARD ACCESSORIES**

1. Lubricating device for headstock	1 set	8. Tool post screw wrench	1 set
2. Spindle motor: 30 HP	1 set	9. Level pads	1 set
3. Magnetic brake	1 set	10. Tools & tool box	1 set
4. Longitudinal & cross rapid feeding	1 set	11. Operation manual	1 set
5. X,Z-axes auto lubrication	1 set		1 set
6. X,Z-axes with Turcite-B	1 set		
7. Face plate with 4 jaws 60"	1 set		

**OPTIONAL ACCESSORIES**

1. Coolant device	4. Spindle bore (230 mm) 9"
2. Face plate with 4 jaw 70"	5. Spindle nose : A2-20
3. Spindle nose : A2-15	


**DENVER IND. CO., LTD.**  
**銘全工業股份有限公司**

AGENT / 代理商

41464 台灣台中縣烏日鄉溪南路一段986巷258號  
 258, Lane 986, Sec1, Shi-Nan Rd., Wu Jih, Taichung 41464 Taiwan  
 TEL: 886-4-2335-4989 FAX: 886-4-2335-4969  
 E-mail: denver@ms77.hinet.net http://www.topdenver.com



# DENVER

## HEAVY DUTY FACING LATHE

Specially made


**HF -1500 / 2000 / 2500**
**x 1000**

-- The standard is without gear box.